

DERWENT-ACC-NO: 2005-182192

DERWENT-WEEK: 200519

COPYRIGHT 2005 DERWENT INFORMATION LTD

TITLE: Vacuum cleaner comprises a housing and an exhaust opening for an exhaust flow connected to the pressurized side of a motor/fan arrangement via a flow channel to divide the exhaust flow into partial channels

INVENTOR: BOTT, E; ILLIG, R ; NIEDERGESAEISS, A

PATENT-ASSIGNEE: BSH BOSCH & SIEMENS HAUSGERAETE GMBH[BSHB]

PRIORITY-DATA: 2003DE-1036828 (August 11, 2003)

PATENT-FAMILY:

| PUB-NO | PUB-DATE | LANGUAGE | PAGES | MAIN-IPC |
|------------------|-------------------|----------|-------|-------------|
| DE 10336828 A1 | March 10, 2005 | N/A | 000 | A47L 009/00 |
| WO 2005016106 A1 | February 24, 2005 | G | 025 | A47L 009/00 |

DESIGNATED-STATES: AE AG AL AM AT AU AZ BA BB BG BR BW BY BZ CA CH CN CO
CR CU
CZ DK DM DZ EC EE EG ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ
LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NA NI NO NZ OM PG PH PL PT RO
RU
SC SD SE SG SK SL SY TJ TM TN TR TT TZ UA UG US UZ VC VN YU ZA ZM ZW AT BE BG
BW CH CY CZ DE DK EA EE ES FI FR GB GH GM GR HU IE IT KE LS LU MC MW MZ NA NL
OA PL PT RO SD SE SI SK SL SZ TR TZ UG ZM ZW

APPLICATION-DATA:

| PUB-NO | APPL-DESCRIPTOR | APPL-NO | APPL-DATE |
|----------------|-----------------|----------------|-----------------|
| DE 10336828A1 | N/A | 2003DE-1036828 | August 11, 2003 |
| WO2005016106A1 | N/A | 2004WO-EP08952 | August 10, 2004 |

INT-CL (IPC): A47L005/00, A47L009/00

ABSTRACTED-PUB-NO: WO2005016106A

BASIC-ABSTRACT:

NOVELTY - Vacuum cleaner comprises a housing and an exhaust opening for an exhaust flow connected to the pressurized side of a motor/fan arrangement (27) via a flow channel to divide the exhaust flow into a first partial channel (33) and a second partial channel. The first partial channel and the second partial

channel are arranged in front of the exhaust opening.

DETAILED DESCRIPTION - Preferred Features: The second partial channel is connected to the first partial channel on the downstream side. The second partial channel forms a secondary flow channel which opens into the first partial channel forming a main flow channel.

USE - Vacuum cleaner.

ADVANTAGE - Noise is reduction during operation of the vacuum cleaner without using additional complex baffle devices.

DESCRIPTION OF DRAWING(S) - The drawing shows a cross-section through the vacuum cleaner.

motor/fan arrangement 27

first partial channel 33

filter 35

first side wall section 56

second side wall section 57

CHOSEN-DRAWING: Dwg.3/5

TITLE-TERMS: VACUUM CLEAN COMPRISE HOUSING EXHAUST OPEN EXHAUST FLOW CONNECT

PRESSURISED SIDE MOTOR FAN ARRANGE FLOW CHANNEL DIVIDE EXHAUST FLOW CHANNEL

DERWENT-CLASS: P28 X27

EPI-CODES: X27-D04;

SECONDARY-ACC-NO:

Non-CPI Secondary Accession Numbers: N2005-152002

